

Wish you a happy & PROSPEROUS NEW YEAR

To
All Our Esteemed Customers

Vamshi Rubber Ltd wishes all our customers a Happy and Prosperous New Year. We wish that your business opportunities will grow as compared to last year and the New Year will bring good financial returns and satisfaction. We at Vamshi assure you with all our best efforts to make your business a success. We thank all our customers for their continuous patronage and support which is instrumental to our company success and growth.

Hope the impact due to demonetization will go and normalization returns in the New Year.

TIP OF THE DAY:

Tread Lift

Appearance: The complete tread peels away from the tyre casing mostly without cushion gum immediately after curing or within few kilometers once the tyre is running.

Cause: Extremely low bonding strength between cushion and tread due to usage of already set or time expired cushion gum, lack of enough Tube pressure, zero differential pressure, lack of enough quantity of steam due to blocked or in-efficient boiler operation.

Remedy: Very often the problem is encountered within in a short time after the tyre is put to use. If the problem is identified in time and tyre is returned before the casing crown area gets damaged the tyre can be retreaded again. If the tread is not damaged then the tread can be reused.



Please ensure that curing temperature, curing time, tube & chamber pressure or steam pressure are maintained properly. Also there must be a difference between chamber pressure and tube pressure i.e; at least 1.5 to 2kg/cm² (20 to 30 PSI), so as to give good bonding strength. Otherwise the cure will be completed without sufficient bonding strength.




We have developed the following Sizes for our Domestic and International Customers.

● VAMSHI TRAILER SPECIAL (VTS)

Traction Characteristics:

Real Axle, Good Traction, Good Performance.



Code	Tread Width (mm)	Tread Thickness (mm)	Non Skid Depth (mm)	Length per Tread (mm)	Under Tread Thickness (mm)	No. of Treads per Roll	Approx Weight per Tread (kg.)	Approx Weight per Package (kg.)	Applications Tyre Sizes Used on
VTS - 310	310	16.40	13.60	3300 mm (130")	2.80	2	16.00	32.00	385/65R22.5 SUPER SINGLES
VTS - 310 XL	310	16.40	13.60	3400 mm (134")	2.80	2	16.48	32.96	385/65R22.5 SUPER SINGLES

We have developed the following Sizes for our Domestic and International Customers.

● VAMSHI DRIVE HEAVY DUTY (VDHD)

Traction Characteristics:

All Wheel, Good Traction High Performance.



Code	Tread Width (mm)	Tread Thickness (mm)	Non Skid Depth (mm)	Length per Tread (mm)	Under Tread Thickness (mm)	No. of Treads per Roll	Approx Weight per Tread (kg.)	Approx Weight per Package (kg.)	Applications Tyre Sizes Used on
VDHD-220	220	18.00	15.00	3300 mm (130")	3.00	2	17.60	35.20	385/65R22.5, 315/80R22.5 RADIAL ONLY
VDHD-220 SL	220	18.00	15.00	3250 mm (128")	3.00	3	11.62	34.86	385/65R22.5, 315/80R22.5 RADIAL ONLY
VDHD-220 XL	220	18.00	15.00	3400 mm (134")	3.00	2	18.13	36.26	385/65R22.5, 315/80R22.5 RADIAL ONLY
VDHD-230	230	18.00	15.00	3300 mm (130")	3.00	3	12.40	37.20	10.00R20, 11.00R22.5 RADIAL ONLY
VDHD-230 SL	230	18.00	15.00	3250 mm (128")	3.00	3	12.20	36.60	10.00R20, 11.00R22.5 RADIAL ONLY
VDHD-230 XL	230	18.00	15.00	3400 mm (134")	3.00	3	12.77	38.31	10.00R20, 11.00R22.5 RADIAL ONLY
VDHD-240	240	24.20	21.00	3300 mm (130")	3.20	2	17.60	35.20	385/65R22.5, 315/80R22.5 RADIAL ONLY
VDHD-240 SL	240	24.20	21.00	3250 mm (128")	3.20	2	17.33	34.66	385/65R22.5, 315/80R22.5 RADIAL ONLY
VDHD-240 XL	240	24.20	21.00	3400 mm (134")	3.20	2	18.13	36.26	385/65R22.5, 315/80R22.5 RADIAL ONLY
VDHD - 250	250	24.30	21.00	3300 mm (130")	3.30	2	18.30	36.6	295/80R22.5, 315/80R22.5 RADIAL ONLY
VDHD-250 SL	250	24.30	21.00	3250 mm (128")	3.30	2	18.00	36.00	295/80R22.5, 315/80R22.5 RADIAL ONLY
VDHD-250 XL	250	24.30	21.00	3400 mm (134")	3.30	2	18.85	37.70	295/80R22.5, 315/80R22.5 RADIAL ONLY
VDHD - 260	260	24.30	21.00	3300 mm (130")	3.30	2	19.10	38.20	385/65R22.5, 315/80R22.5 RADIAL ONLY
VDHD-260 XL	260	24.30	21.00	3400 mm (134")	3.30	2	19.70	39.40	385/65R22.5, 315/80R22.5 RADIAL ONLY
VDHD - 270	270	24.40	21.00	3300 mm (130")	3.40	2	19.90	39.80	385/65R22.5, 315/80R22.5 RADIAL ONLY
VDHD-270 XL	270	24.40	21.00	3400 mm (134")	3.40	2	20.50	41.00	385/65R22.5, 315/80R22.5 RADIAL ONLY

Hope you liked this NEWSLETTER. We solicit your feed back for improvisation.

Your sincerely,

R. SURENDRA REDDY
Managing Director

AN ISO 9001:2008
CERTIFIED COMPANY