
VAMSHI TREADS

PRODUCT BROCHURE

HIGHWAY LUG RADIAL (HLR)




| Traction Characte | ristics: | Exceller | t Tractio | n, RearAx | le, High P | erforma | nce | |
|-------------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|---------------------|
| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
| HLR 187-120 | 187 | 120 | 3050 | 14.40 | 9.50 | 3 | 28.50 | 8.25-R-16 |
| HLR 205-127 | 205 | 127 | 3225 | 14.00 | 11.25 | 3 | 33.75 | 9.00-R-20 |
| HLR 210-127 | 210 | 127 | 3225 | 14.00 | 11.40 | 3 | 34.20 | 10.00-R-20 |
| HLR 210-128 | 210 | 128 | 3250 | 14.00 | 11.50 | 3 | 34.50 | 10.00-R-20 |
| HLR 215-127 | 215 | 127 | 3225 | 13.90 | 11.55 | 3 | 34.65 | 10.00-R-20 |
| HLR 215-128 | 215 | 128 | 3250 | 13.90 | 11.65 | 3 | 34.95 | 10.00-R-20 |
| HLR 220-128 | 220 | 128 | 3240 | 13.80 | 11.85 | 3 | 35.55 | 10.00-R-20 |
| HLR 220-130 | 220 | 130 | 3300 | 13.80 | 12.10 | 3 | 36.30 | 10.00-R-20 |
| HLR 220-H-126 | 220 | 126 | 3200 | 18.10 | 14.85 | 2 | 29.70 | 10.00-R-20 |
| HLR 220-H-130 | 220 | 130 | 3300 | 18.10 | 15.30 | 2 | 30.60 | 10.00-R-20 |
| HLR 220-R-128 | 220 | 128 | 3250 | 13.20 | 11.30 | 3 | 33.90 | 10.00-R-20 |

^{*} Commercial Tolerance <u>+</u> 2% is to be allowed

HIGHWAY RADIAL (HWR) RADIAL ONLY

| Traction Characte | ristics: | Free Ro | lling, All | Wheel, Ex | cellent Pe | erforman | ce | |
|-------------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--|
| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | Sizes |
| HWR 200-096 | 200 | 96 | 2450 | 10.50 | 6.52 | 5 | 32.60 | 235/75-R-17.5 |
| HWR 205-096 | 205 | 96 | 2450 | 12.60 | 7.50 | 4 | 30.00 | 235/75-R-17.5 |
| HWR 205-099 | 205 | 99 | 2525 | 12.60 | 7.70 | 4 | 30.80 | 235/75-R-17.5 |
| HWR 205-128 | 205 | 128 | 3250 | 12.60 | 9.90 | 3 | 29.70 | 9.00-R-20 10.00-R-20 |
| HWR 210-127 | 210 | 127 | 3225 | 13.90 | 11.25 | 3 | 33.75 | 10.00-R-20 |
| HWR 210-130 | 210 | 130 | 3300 | 13.90 | 11.50 | 3 | 34.50 | 10.00-R-20 11.00-R-20 |
| HWR 215-127 | 215 | 127 | 3225 | 13.70 | 11.65 | 3 | 34.95 | 10.00-R-20 |
| HWR 215-128 | 215 | 128 | 3250 | 13.70 | 11.75 | 3 | 35.25 | 10.00-R-20 |
| HWR 215-130 | 215 | 130 | 3300 | 13.70 | 11.92 | 3 | 35.76 | 10.00-R-20 11.00-R-20 |
| HWR 220-127 | 220 | 127 | 3225 | 13.25 | 11.44 | 3 | 34.32 | 10.00-R-20 |
| HWR 220-130 | 220 | 130 | 3300 | 13.25 | 11.70 | 3 | 35.10 | 10.00-R-20 11.00-R-20 |
| HWR 220-134 | 220 | 134 | 3400 | 13.25 | 12.05 | 3 | 36.15 | 10.00-R-20 11.00-R-20 |
| HWR 220-H-127 | 220 | 127 | 3225 | 14.50 | 12.15 | 3 | 36.45 | 10.00-R-20 |
| HWR 220-H-129 | 220 | 129 | 3275 | 14.50 | 12.35 | 3 | 37.05 | 10.00-R-20 11.00-R-20 |
| HWR 225-127 | 225 | 127 | 3225 | 14.30 | 12.35 | 3 | 37.05 | 10.00-R-20 |
| HWR 230-128 | 230 | 128 | 3240 | 13.00 | 12.10 | 3 | 36.30 | 10.00-R-20 |
| HWR 230-130 | 230 | 130 | 3300 | 13.00 | 12.35 | 3 | 37.05 | 10.00-R-20 11.00-R-20 |
| HWR 230-134 | 230 | 134 | 3400 | 13.00 | 12.70 | 3 | 38.10 | 10.00-R-20 11.00-R-20 |
| HWR 240-127 | 240 | 127 | 3225 | 12.80 | 12.25 | 3 | 36.75 | 11-R-22.5 295/80-R-22.5 |
| HWR 240-130 | 240 | 130 | 3300 | 12.80 | 12.50 | 3 | 37.50 | 11-R-22.5 295/80-R-22.5 |
| HWR 240-134 | 240 | 134 | 3400 | 12.80 | 12.85 | 3 | 38.55 | 11-R-22.5 295/80-R-22.5 |
| HWR 240-R-130 | 238 | 130 | 3300 | 9.80 | 10.00 | 3 | 30.00 | 10.00-R-20 11.00-R-20 12.00-R-20 295/850-R-22.5 |
| HWR 250-126 | 250 | 126 | 3200 | 14.00 | 13.60 | 2 | 27.20 | 295/80-R-22.5 |
| HWR 250-130 | 250 | 130 | 3300 | 14.00 | 14.03 | 2 | 28.06 | 295/80-R-22.5 |
| HWR 250-134 | 250 | 134 | 3400 | 14.00 | 14.45 | 2 | 28.90 | 295/80-R-22.5 |

^{*} Commercial Tolerance <u>+</u> 2% is to be allowed




Traction Characteristics: Free Rolling, All Wheel, High Performance, Light Truck

| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
|--------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|------------------|
| RTT 174-087 | 174 | 87 | 2210 | 11.30 | 5.05 | 6 | 30.30 | 215/75-R-15 |

* Commercial Tolerance <u>+</u> 2% is to be allowed

TRIALWAY RADIAL (TWR)

RADIAL ONLY



Traction Characteristics: Free Rolling, All Wheel, High Speed, High Performance

| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
|--------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--------------------------|
| TWR 219-127 | 219 | 127 | 3215 | 10.50 | 9.80 | 3 | 29.40 | 10.00-R-20 |
| TWR 219-130 | 219 | 130 | 3300 | 10.50 | 10.05 | 3 | 30.15 | 10.00-R-20 11.00-R-20 |

| ULTRA GRIP RADIAL (UGR) | RADIAL ONLY |
|-------------------------|--|
| | A The State of the |
| (a) Carried Figure | [O [VAXHUR] LI |
| | |
| | |

| Traction Characteristics: | Rear Axle. | Good Traction. | High Performance |
|---------------------------|------------|----------------|------------------|
|---------------------------|------------|----------------|------------------|

| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
|--------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--------------------------|
| UGR 210-130 | 210 | 130 | 3300 | 14.60 | 11.20 | 3 | 33.60 | 10.00-R-20 |
| UGR 219-130 | 219 | 130 | 3300 | 13.50 | 11.15 | 3 | 33.45 | 10.00-R-20 11.00-R-20 |

* Commercial Tolerance <u>+</u> 2% is to be allowed

VAMSHI DIRECTIONAL RADIAL(VDR)



Traction Characteristics: Rear Axle, Good Traction, High Performance, Mixed Service

| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
|--------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--------------------------|
| VDR 220-130 | 220 | 130 | 3300 | 15.00 | 12.65 | 3 | 37.95 | 10.00-R-20 11.00-R-20 |
| VDR 230-130 | 230 | 130 | 3300 | 15.00 | 13.30 | 2 | 26.60 | 10.00-R-20 11.00-R-20 |

^{*} Commercial Tolerance <u>+</u> 2% is to be allowed

| VAMSHI HIGH SPEED RADIAL(VHSR) | RADIAL ONLY |
|--|--|
| The state of the s | with the same of the same of the same of |
| | |
| | |

Traction Characteristics: Free Rolling, All Wheel, Excellent Performance

| | | 17.5 | . | , | | | 200 | |
|--------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|------------------|
| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
| VHSR 215-128 | 215 | 128 | 3240 | 11.50 | 10.20 | 3 | 30.60 | 10.00-R-20 |

* Commercial Tolerance <u>+</u> 2% is to be allowed

VAMSHI RADIAL ALL WHEEL(VRAW) RADIAL ONLY

Traction Characteristics: Free Rolling, All Wheel, High Performance

| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
|--------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--------------------------|
| VRAW 215-128 | 215 | 128 | 3250 | 13.10 | 10.95 | 3 | 32.85 | 10.00-R-20 |
| VRAW 220-128 | 220 | 128 | 3250 | 13.60 | 11.45 | 3 | 34.35 | 10.00-R-20 11.00-R-20 |

VAMSHI RADIAL CHALLENGE (VRC)

RADIAL ONLY

| afairefundendendendendendendendendendendendenden |
|--|
| and proving an international control of the control |
| |
| I have been been been been been been been be |
| De la principal de la constantia del constantia del constantia del constantia del constantia della constanti |
| |
| the state of the s |
| |
| |
| |
| for the first to the fortest to the total a fortest a land a land |


Traction Characteristics: Free Rolling, All Wheel, Good Traction, High Performance

| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
|--------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|---------------------|
| VRC 215-128 | 215 | 128 | 3250 | 12.7 | 10.7 | 3 | 32.10 | 10.00-R-20 |
| VRC 215-131 | 215 | 131 | 3330 | 12.7 | 10.95 | 3 | 32.85 | 10.00-R-20 |
| VRC 220-128 | 220 | 128 | 3260 | 12.50 | 10.95 | 3 | 32.85 | 10.00-R-20 |

* Commercial Tolerance <u>+</u> 2% is to be allowed

VAMSHI RADIAL HIGHWAY (VRH)

RADIAL ONLY



Traction Characteristics: Free Rolling, All Wheel, High Performance

| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
|--------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--------------------------|
| VRH 220-129 | 220 | 129 | 3275 | 13.10 | 11.65 | 3 | 34.95 | 10.00-R-20 11.00-R-20 |

VAMSHI RADIAL EXCEL (VRE)

| the state of the s | the desired of the second | The state of | the state of | And the state of | The state of | 444 | 4 |
|--|--|--------------|--------------|------------------|--------------|--------|----------|
| THE THE PARTY OF T | | بالباليال | - delighe | The Table | 444 | 444 | 704 |
| الماليالياليالياليالياليالياليالياليالياليا | | واسام واسام | والماراليال | | 4 | البليا | 2 |
| al al al | | July 1 | The state of | le de le | | | عليك |
| | | 1515151 | 15/5/5/2 | RRRR | 666 | 13/3/ | |
| Į | all and Designation of the Control o | | | | التلالت | | Con land |

| Traction Characte | eristics: | Free Ro | Free Rolling, All Wheel, Excellent Performance | | | | | | | | |
|-------------------|-----------|-----------------|--|-------------------|---------------------|--------------------|-------------------|-------------------------------|--|--|--|
| Product Code | Tread | Tread Length | Tread Length | Non-Skid Depth | Weight per Tread | Treads Per Roll | Roll Weight (kgs) | For Tyre / Sizes | | | |
| VRE 200-096 | 200 | 96 | 2450 | 14.00 | 8.30 | 4 | 33.20 | 235/75-R-17.5 | | | |
| VRE 205-127 | 205 | 127 | 3235 | 13.50 | 11.05 | 3 | 33.15 | 9.00-R-20 | | | |
| VRE 210-127 | 210 | 127 | 3235 | 14.00 | 11.63 | 3 | 34.89 | 9.00-R-20 10.00-R-20 | | | |
| VRE 215-127 | 215 | 127 | 3235 | 14.15 | 11.75 | 3 | 35.25 | 10.00-R-20 | | | |
| VRE 215-130 | 215 | 130 | 3300 | 14.15 | 11.98 | 3 | 35.94 | 10.00-R-20 11.00-R-20 | | | |
| VRE 225-127 | 225 | 127 | 3235 | 13.65 | 12.50 | 3 | 37.50 | 10.00-R-20 11.00-R-20 | | | |
| VRE 225-130 | 225 | 130 | 3300 | 13.65 | 12.75 | 3 | 38.25 | 10.00-R-20 11.00-R-20 | | | |
| VRE 240-129 | 240 | 129 | 3280 | 16.00 | 14.25 | 2 | 28.50 | 11.00-R-22.5 295/80-R-22.5 | | | |
| VRE 245-130 | 245 | 130 | 3300 | 14.00 | 13.80 | 2 | 27.60 | 295/80-R-22.5 | | | |

^{*} Commercial Tolerance <u>+</u> 2% is to be allowed

VAMSHI RADIAL LONG DRIVE (VRLD) RADIAL ONLY Traction Characteristics: Rear Wheel, Good Traction, High Performance Tread Non-Skid Tread Tread Treads Weight Roll Weight For Tyre / **Product Code** width Length Length Depth Per Roll per Tread Sizes (kgs) (mm) (Inch) (mm) (mm) (kgs) 8.25-R-16 12.00 VRLD 175-118 175 118 3000 7.60 4 30.40 8.25-R-20 VRLD 210-128 210 128 3245 13.30 10.90 3 32.70 10.00-R-20 VRLD 215-128 215 3245 14.00 3 34.20 128 11.40 10.00-R-20 VRLD 215-R-128 215 128 3250 13.20 10.80 3 32.40 10.00-R-20 VRLD 215-130 215 130 3300 14.00 11.59 3 34.77 10.00-R-20 VRLD 220-128 220 128 3250 14.00 11.75 3 35.25 10.00-R-20 VRLD 220-R-128 220 128 3250 13.10 10.98 3 32.94 10.00-R-20 VRLD 220-130 220 130 3300 14.00 11.90 3 35.70 10.00-R-20 230 127 3225 14.00 12.10 3 36.30 VRLD 230-127 10.00-R-20 12.35 VRLD 230-129 230 129 3285 14.00 3 37.05 10.00-R-20 VRLD 230R-129 230 129 3280 12.80 11.60 3 34.80 10.00-R-20 VRLD 230-133 230 133 3390 14.00 12.75 3 38.25 11.00-R-20 VRLD 230R-134 230 134 3400 12.80 12.00 3 36.00 11.00-R-20 10.00-R-20 VRLD 240-132 240 132 3340 13.00 12.40 3 37.20 11.00-R-20 10.00-R-20 3400 VRLD 240-134 240 134 13.00 12.62 3 37.86 11.00-R-20

| VAMSHI RADIAL PRIDE (VRP) | RADIAL ONLY |
|--|-------------|
| | THE TENED |
| 2222222222222 | |
| de de la contraction de la con | ideal |
| | LILITITI |


Traction Characteristics: Free Rolling, Rear Wheel, Good Traction, High Performance

| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
|--------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--------------------------|
| VRP 215-128 | 215 | 128 | 3260 | 14.50 | 11.35 | 3 | 34.05 | 10.00-R-20 |
| VRP 220-128 | 220 | 128 | 3260 | 14.50 | 11.60 | 3 | 34.80 | 10.00-R-20 11.00-R-20 |
| VRP 220-131 | 220 | 131 | 3325 | 14.50 | 11.83 | 3 | 35.49 | 10.00-R-20 11.00-R-20 |
| VRP 230-128 | 230 | 128 | 3260 | 14.50 | 11.95 | 3 | 35.85 | 10.00-R-20 11.00-R-20 |
| VRP 230-131 | 230 | 131 | 3325 | 14.50 | 12.20 | 3 | 36.60 | 10.00-R-20 11.00-R-20 |

^{*} Commercial Tolerance <u>+</u> 2% is to be allowed

VAMSHI RADIAL RIB (VRR)

RADIAL ONLY



Traction Characteristics: Free Rolling, All Wheel, Excellent Performance

| Traction onaracter | raction onaracteristics. Tree Rolling, All Wheel, Excellent refrontiance | | | | | | | | | |
|--------------------|--|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--------------------------|--|--|
| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes | | |
| VRR 210-127 | 210 | 127 | 3225 | 13.50 | 11.40 | 3 | 34.20 | 10.00-R-20 | | |
| VRR 210-130 | 210 | 130 | 3300 | 13.50 | 11.65 | 3 | 34.95 | 10.00-R-20 11.00-R-20 | | |
| VRR 220-127 | 220 | 127 | 3225 | 14.10 | 12.45 | 3 | 37.35 | 10.00-R-20 | | |
| VRR 220-128 | 220 | 128 | 3250 | 14.10 | 12.55 | 3 | 37.65 | 10.00-R-20 | | |
| VRR 220-130 | 220 | 130 | 3300 | 14.10 | 12.75 | 3 | 38.25 | 10.00-R-20 11.00-R-20 | | |
| VRR 220-H-130 | 220 | 130 | 3300 | 18.00 | 15.00 | 2 | 30.00 | 10.00-R-20 11.00-R-20 | | |
| VRR 220-R-127 | 220 | 127 | 3225 | 13.00 | 11.35 | 3 | 34.05 | 10.00-R-20 | | |
| VRR 220-R-128 | 220 | 128 | 3250 | 13.00 | 11.45 | 3 | 34.35 | 10.00-R-20 | | |
| VRR 220-R-130 | 220 | 130 | 3300 | 13.00 | 11.60 | 3 | 34.80 | 10.00-R-20 11.00-R-20 | | |
| VRR 230-130 | 230 | 130 | 3300 | 14.10 | 13.30 | 2 | 26.60 | 10.00-R-20 11.00-R-20 | | |
| VRR 230-H-130 | 230 | 130 | 3300 | 18.00 | 15.70 | 2 | 31.40 | 10.00-R-20 11.00-R-20 | | |

^{*} Commercial Tolerance <u>+</u> 2% is to be allowed

| VAMSHI RADIAL SUPREME (VRS) | RADIAL ONLY |
|--|-------------|
| | |
| and the first of the first of the | |
| Light of the first of the first of the of the of | 17777 |
| The state of the s | J. L. L. L. |

| Traction Characte | eristics: | Free Ro | Free Rolling, All Wheel, High Performance | | | | | | | | |
|-------------------|------------------------|---------------------------|---|---------------------------|---------------------|-----------------------------|----------------------|-------------------------|--|--|--|
| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes | | | |
| VRS 205-127 | 205 | 127 | 3235 | 14.00 | 11.35 | 3 | 34.05 | 9.00-R-20 10.00-R-20 | | | |
| VRS 210-127 | 210 | 127 | 3235 | 14.00 | 11.70 | 3 | 35.10 | 10.00-R-20 | | | |

^{*} Commercial Tolerance <u>+</u> 2% is to be allowed

VAMSHI RADIAL SUPER DRIVE (VRSD)

RADIAL ONLY

| n lage lage lage lage lage | Land and Land and Land and Land | |
|----------------------------|---------------------------------|----------------|
| | | tetetetetetete |

Traction Characteristics: Excellent Traction, RearAxle, High Performance

| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
|----------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--------------------------|
| VRSD 215-128 | 215 | 128 | 3245 | 13.70 | 11.35 | 3 | 34.05 | 10.00-R-20 11.00-R-20 |
| VRSD 220-128 | 220 | 128 | 3250 | 14.00 | 11.95 | 3 | 35.85 | 10.00-R-20 11.00-R-20 |
| VRSD 220-R-128 | 220 | 128 | 3250 | 13.20 | 11.45 | 3 | 34.35 | 10.00-R-20 11.00-R-20 |

^{*} Commercial Tolerance <u>+</u> 2% is to be allowed

VAMSHI RADIAL XPRESS (VRX) RADIAL ONLY

Free Rolling, All Wheel, High Performance Traction Characteristics: Tread Tread Non-Skid Tread Treads Weight Roll Weight For Tyre / **Product Code** width Length Length Depth Per Roll per Tread Sizes (kgs) (Inch) (mm) (mm) (mm) (kgs) 9.00-R-20 205 VRX 205-127 127 3225 13.20 9.90 3 29.70 10.00-R-20 VRX 215-128 215 128 3250 13.10 11.05 3 33.15 10.00-R-20 10.00-R-20 VRX 220-127 220 127 3225 13.80 11.10 3 33.30 11.00-R-20 10.00-R-20

13.80

11.20

3

33.60

11.00-R-20

VRX 220-128

220

128

3250

^{*} Commercial Tolerance <u>+</u> 2% is to be allowed

| VAMSHI | RAD | IAL Z | ZIGM | A (VI | 7Z) | | RADIA | L ONLY |
|-------------------|------------------------|---------------------------|-------------------------|---------------------------|------------------------|-----------------------------|----------------------|--------------------------|
| | | 1 | | 7 1-7 | | | | |
| | 1 | | 1 | 1 | | 1 | | |
| Traction Characte | ristics: | rree Ro | ling, All | Wheel, Hi | gn Perrori | mance | | |
| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
| VRZ 240-129 | 240 | 129 | 3270 | 12.40 | 12.23 | 3 | 36.69 | 10.00-R-20 11.00-R-20 |
| VRZ 240-131 | 240 | 131 | 3315 | 12.40 | 12.40 | 3 | 37.20 | 10.00-R-20 11.00-R-20 |
| | * Com | ı <mark>mercia</mark> | <mark>l Tolera</mark> | nce <u>+</u> 2° | <mark>% is to b</mark> | e allov | /ed | |



Traction Characteristics: Rear Axle, Good Traction, Good Performance

| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
|--------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--------------------------|
| VSHT 220-130 | 220 | 130 | 3300 | 16.00 | 13.05 | 3 | 39.15 | 10.00-R-20 11.00-R-20 |

| Traction Characte | eristics: | Free Ro | lling, All | Wheel, Hi | gh Perfor | mance | | |
|-------------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--------------------------|
| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
| VSR 210-127 | 210 | 127 | 3225 | 13.60 | 11.05 | 3 | 33.15 | 10.00-R-20 |
| VSR 215-127 | 215 | 127 | 3225 | 13.50 | 11.55 | 3 | 34.65 | 10.00-R-20 |
| VSR 215-128 | 215 | 128 | 3250 | 13.50 | 11.65 | 3 | 34.95 | 10.00-R-20 |
| VSR 215-130 | 215 | 130 | 3300 | 13.50 | 11.80 | 3 | 35.40 | 10.00-R-20 11.00-R-20 |
| VSR 220-128 | 220 | 128 | 3240 | 14.00 | 12.50 | 3 | 37.50 | 10.00-R-20 |
| VSR 220-130 | 220 | 130 | 3300 | 14.00 | 12.75 | 3 | 38.25 | 10.00-R-20 11.00-R-20 |
| VSR 220-H-129 | 220 | 129 | 3270 | 18.00 | 14.70 | 2 | 29.40 | 10.00-R-20 11.00-R-20 |
| VSR 220-R-127 | 220 | 127 | 3225 | 13.30 | 11.35 | 3 | 34.05 | 10.00-R-20 11.00-R-20 |
| VSR 220-R-128 | 220 | 128 | 3250 | 13.30 | 11.45 | 3 | 34.35 | 10.00-R-20 11.00-R-20 |
| VSR 220-R-130 | 220 | 130 | 3300 | 13.30 | 11.60 | 3 | 34.80 | 10.00-R-20 11.00-R-20 |
| VSR 220-R-132 | 220 | 132 | 3365 | 13.30 | 11.86 | 3 | 35.58 | 11.00-R-20 |
| VSR 230-129 | 230 | 129 | 3270 | 14.60 | 13.35 | 2 | 26.70 | 10.00-R-20 11.00-R-20 |
| VSR 230-H-129 | 230 | 129 | 3270 | 18.10 | 15.40 | 2 | 30.80 | 10.00-R-20 11.00-R-20 |
| VSR 230-R-128 | 230 | 128 | 3240 | 12.80 | 11.75 | 3 | 35.25 | 10.00-R-20 |
| VSR 230-R-130 | 230 | 130 | 3300 | 12.80 | 12.00 | 3 | 36.00 | 10.00-R-20 11.00-R-20 |

^{*} Commercial Tolerance <u>+</u> 2% is to be allowed

| VAMSHI TRAILER PLUS (VTP) | RADIAL ONLY |
|---|--|
| A PARTY OF THE PROPERTY OF THE PARTY OF THE | A CONTRACTOR OF THE CONTRACTOR |
| ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~ | |
| | |
| | |

| Product Code | Tread width (mm) | Tread Length (Inch) | Tread Length (mm) | Non-Skid Depth (mm) | Weight per Tread | Treads Per Roll (kgs) | Roll Weight (kgs) | For Tyre / Sizes |
|--------------|------------------------|---------------------------|-------------------------|---------------------------|---------------------|-----------------------------|----------------------|--------------------------|
| VTP 220-127 | 220 | 127 | 3225 | 14.70 | 12.70 | 3 | 38.10 | 10.00-R-20 |
| VTP 220-130 | 220 | 130 | 3300 | 14.70 | 13.00 | 3 | 39.00 | 10.00-R-20 11.00-R-20 |

^{*} Commercial Tolerance <u>+</u> 2% is to be allowed